

Referências Bibliográfica

- [1] N. Benvenuto, L. Tomba, *Performance Comparison of Space Diversity and Equalization Techniques for indoor Radio Systems*, IEEE Transactions on Vehicular Technology, volume 40, número 2, págs. 358-368, maio de 1997;
- [2] D.S. Polydorou, C.N. Capsalis, *A New Theoretical Model for the Prediction of Rapid Fading Variations in an Indoor Environment*, IEEE Transactions on Vehicular Technology, volume 46, número 3, págs. 748-754, agosto de 1997;
- [3] R.D. Murch, K.W. Cheung, M.S. Fong, J.H.M. Sau e J.C-I Chuang, *A New Approach to Indoor Propagation Prediction*, IEEE págs. 1737-1740;
- [4] R.A. Valenzuela, O. Landron, D.L.Jacobs, *Estimating Local Mean Signal Strength of Indoor Multipath Propagation*, IEEE Transactions on Vehicular Technology, volume 46, número 1, págs. 203-212, Fevereiro de 1997;
- [5] William C. Y. Lee, *Mobile Communications Design Fundamentals*, Mcgraw Hill Bo. Co,1992.
- [6]
- [7] Saleh Faruque, *Cellular Mobile Systems Engineering*, Artech House INC, pag. 133, 1992;
- [8] Y.P. Zhang, Y. Hwang, *Measurements of the Characteristics of Indoor Penetration Loss*, IEEE, , págs. 1741-1744,1994;
- [9] T. Schwengler, M. Gilbert, *Propagation Models at 5.8 GHz – Path Loss & Building Penetration*, IEEE, págs. 119-124, 2000;
- [10] Iñigo Cuiñas, M.G. Sánchez, *Measurement of Transmission Coefficients of Radiowaves Through Building Materials in the 5.8 GHz Frequency Band*, in Proc. 1999 IEEE AP-S Int. Symp., Orlando, FL, págs. 1474-1477, julho de 1999;

- [11] P.F.M. Smulders, .A.G. Wagemans, *Wideband Indoor Radio Propagation Measurements at 58 GHz*, *Electronic Letters*, volume 28, número 13, págs. 1270-1272, junho 1992;
- [12] Mitsuyuki Oda, *Radio Wave Absorptive Building Materials for Depressing Multipath Indoors*,
- [13] Simon R. Saunders, *Antennas and Propagation for Wireless Communication Systems*, John Wiley & Sons Ltd, págs. 271-277, dezembro de 1999;
- [14] F.A. Agelet, Arno Formella, J.M.H. Rábanos, F.I. de Vicente e F.P. Fóntan, *Efficient Ray-Tracing Acceleration Techniques for Radio Propagation Modeling*, *IEEE Transactions on Vehicular Technology*, volume 46, número 6, págs. 2089-2104, novembro de 2000;
- [15] K.A. Remley, H.R. Anderson e A. Weissnar, *Improving the Accuracy of Ray-Tracing Techniques for Indoor Propagation Modeling*, *IEEE Transactions on Vehicular Technology*, volume 49, número 6, págs. 2350-2358, novembro de 2000;
- [16] J. C. Silva, A. G. Neto, J. N. Carvalho, M. S. Alencar, “Determining the Average Penetration Loss: Measurement Procedure and Results” ,proceedings of the 1999 IMOC, International Microwave and Optoelectronics Conference, pp. 240-242, Rio de Janeiro,Brazil, August, 1999.
- [17] E. Kreyszig, *Advanced Engineering Mathematics*, New York: Wiley, seventh edition, 1993.